



# CS401

## FEATURES

- Heavy-duty wide frame
- 2 versions : 400mm blade guard/9HP and 450mm blade guard/13HP
- Continuous depth control with crank handle and gauge
- Removable 20L polyurethane water tank
- Adjustable handle

## BENEFITS

- Low centre of gravity for better direction control
- Two alternatives to fit best user requirements
- Quick, easy and accurate setting of cutting depth.
- Easy wet-cutting in isolated locations
- Ergonomic working position

### CS401 P9

Item No.	701846 47624
EAN 13 Code	5450248 563631

9HP    6,6kW    PETROL

Power source	Petrol
Motor type	Honda GX270
Power kW (Hp)	6,6kW (9 HP)
Blade x bore (mm)	Ø 400 x 25,4
Max. cutting depth (mm)	145
Dimensions (LxWxH) (mm)	1180 x 650 x 1000
Water tank capacity (removable)	20 L
Tool speed RPM	2600 min <sup>-1</sup>
Starter	Recoil
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	3,75 m/s <sup>2</sup>
Sound power / pressure level	100 dB(A)/84 dB(A)
Weight	93kg


### CS401 P13

Item No.	701846 47623
EAN 13 Code	5450248 563624

13HP    9,6kW    PETROL

Power source	Petrol
Motor type	Honda GX390 Cycl.
Power kW (Hp)	9,6kW (13 HP)
Blade x bore (mm)	Ø 450 x 25,4
Max. cutting depth (mm)	170
Dimensions (LxWxH) (mm)	1180 x 650 x 1000
Water tank capacity (removable)	20 L
Tool speed RPM	2600 min <sup>-1</sup>
Starter	Recoil
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	4,13 m/s <sup>2</sup>
Sound power / pressure level	100 dB(A)/86 dB(A)
Weight	99kg


## PRODUCT FEATURES



MAX CUT DEPTH - P9



CUTTING DEPTH INDICATOR



MAX CUT DEPTH - P13



SMART CUTTING-DEPTH LOCKING

## DIAMOND BLADE RECOMMENDATIONS FOR CS401



Substrate / Material	BETON	SILENCIO	ASPHALT	ALL MATERIALS
Recommended Product	EXTREME BETON	EXTREME BETON SILENCIO	EXTREME ASPHALT	PRO 4X4 EXPLORER
CS401 P9	Blade x Bore (mm)	400 x 25,4	400 x 25,4	400 x 25,4
	Item No.	701846 93354	-	701846 02095
CS401 P13	Blade x Bore (mm)	450 x 25,4	450 x 25,4	450 x 25,4
	Item No.	701846 01689	701846 31020	701846 02096
Page reference	18	19	46	36