

# CS451 LOW VIBRATION

## FEATURES

- Handlebar equipped with vibration absorbers
- Handlebar height adjustment settings
- Optimised weight distribution (positioning of motor and tank)
- High capacity water tank (25L)

## BENEFITS

- Improved user comfort
- Ergonomic working position
- Outstanding cutting performance
- Option for wet cutting, even far from water supply



### CS451 P13

Item No. 701846 28433  
EAN 13 Code 5450248 397601



13HP



9,6kW



PETROL

Power source	Petrol
Motor type	HONDA GX390 Cyclonic
Power kW (Hp)	9,6kW (13Hp)
Blade x bore (mm)	Ø 450 x 25,4
Max. cutting depth (mm)	170
Dimensions (LxWxH) (mm)	1180 x 538 x 1040
Water tank capacity (removable)	25 L
Tool speed RPM	2573 min <sup>-1</sup>
Starter	Recoil
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	2,8 m/s <sup>2</sup>
Sound power / pressure level	105 dB (A) / 88 dB (A)
Weight	112kg

### CS451 D7

Item No. 701846 29089  
EAN 13 Code 5450248 399049



7HP



5kW



PETROL

Power source	Diesel
Motor type	HATZ 1B30
Power kW (Hp)	5kW (7Hp)
Blade x bore (mm)	Ø 450 x 25,4
Max. cutting depth (mm)	170
Dimensions (LxWxH) (mm)	1180 x 538 x 1040
Water tank capacity (removable)	25 L
Tool speed RPM	2573 min <sup>-1</sup>
Starter	Recoil
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	4,7 m/s <sup>2</sup>
Sound power / pressure level	110 dB (A) / 91 dB (A)
Weight	120kg

## PRODUCT FEATURES



MAX CUT DEPTH



LOW VIBRATION HANDLEBAR



CUT DEPTH INDICATOR



PULLEYS WITH REMOVABLE HUB AND POLY V-BELTS

## DIAMOND BLADE RECOMMENDATIONS FOR CS451



Substrate / Material	BETON	SILENCIO	ASPHALT	ALL MATERIALS
Recommended Product	EXTREME BETON	EXTREME BETON SILENCIO	EXTREME ASPHALT	PRO 4X4 EXPLORER
Diameter (mm)	450	450	450	450
Bore (mm)	25,4	25,4	25,4	25,4
Item No.	701846 01689	701846 31020	701846 94912	701846 02096
Page reference	18	19	46	36