

# CSB1 P21



## FEATURES

- Heavy duty jig welded steel frame
- Removable water tank
- Automatic forward propulsion
- Manual and hydraulic raise and lower of the blade

## BENEFITS

- Robust and reliable
- Adapt machine to your specific needs
- Better comfort of use
- Quick, easy and accurate depth setting

## PRODUCT DATA

Item No.	701846 45495
EAN 13 Code	5450248 530794

Power source	Petrol
Motor type	HONDA GX630
Power kW (Hp)	15kW (20 Hp)
Blade x bore (mm)	Ø600 x 25,4
Max. cutting depth (mm)	225
Dimensions (LxWxH) (mm)	1200 x 600 x 1100
Weight	240kg

Water tank capacity	Optional ( 25l accessory )
Tool speed RPM	1775 min <sup>-1</sup>
Starter	Electric
Raise and lower	Manual hydraulic
Propelling	Automatic
Hand Arm Vibrations	3,35 m/s <sup>2</sup>
Sound power / pressure level	107 dB(A)/89 dB(A)



20HP



15kW



PETROL

## PRODUCT FEATURES



MAX CUT DEPTH



CONTROL BOX



MANUAL OR HYDRAULIC RAISE & LOWER THE BLADE



REMOVABLE WATER TANK (OPTIONAL)

## DIAMOND BLADE RECOMMENDATIONS FOR CSB1 (PETROL)

Substrate / Material	BETON	BETON	ASPHALT	ASPHALT
Recommended Product	EXTREME BETON	PRO BETON	EXTREME ASPHALT 10	PRO ASPHALT
Diameter (mm)	600	600	600	600
Bore (mm)	25,4	25,4	25,4	25,4
Item No.	701846 01691	701846 11982	701846 40192	701846 11980
Page reference	18	20	46	47