

4-1/2" - 5" Dia. Disc Sanders

.7 hp and 1 hp Models



DISC PADS
PAGE 242

ACCESSORIES
PAGE 222

High-Quality Air-Powered Disc Sanders

FOR ABRASIVE DISCS
4-1/2" (114 mm) to
5" (127 mm) diameters
SEE PAGE 280

Pistol Grip, .7 hp, Rear Exhaust

- Each model includes 50267 Disc Pad Assembly for center-hole abrasive discs, 4-1/2" to 5" in diameter.
- Gearless motor for reduced maintenance and downtime.
- Governor-controlled to maintain RPM under heavy load.
- Removable side handle.

Model 50320 8,000 RPM

Model 50321 11,000 RPM



Model 50320



Dynaswivel® air line connector is ideal for use with most air tools. It improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 223.)



Right: 50321 Pistol-Grip Disc Sander quickly and effectively removes excess fiberglass.



Model 50321

DISC SANDERS

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 50320 | .7 (522) | 8,000 | 72 dB(A) | 30 (850) | 3/8 (10) | 1/4" NPT | 5/8"-11 Male | 2.2 (1.0) | 6-5/8 (168) | 5-5/8 (143) |
| 50321 | .7 (522) | 11,000 | 76 dB(A) | 32 (906) | 3/8 (10) | 1/4" NPT | 5/8"-11 Male | 2.2 (1.0) | 6-5/8 (168) | 5-5/8 (143) |

Tune-Up Kit: No. 96047 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Right Angle, 1 hp, Rear Exhaust

- Extended muffler for reduced sound levels.
- Reversible side handle for left or right hand operation.

5/8"-11 Thread Models

Model 52562 9,000 RPM

- Includes 51150 Disc Pad Assembly.
- 5" diameter.

Model 52561 11,000 RPM

- Includes 51148 Disc Pad Assembly.
- 4-1/2" diameter.

M14 Male Thread Models

- Ideal for use with 115 mm-127 mm diameter Disc Pads with M14 female thread (sold separately).

Model 52564 9,000 RPM

Model 52565 11,000 RPM



Model 52561

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 52561 | 1 (744) | 11,000 | 76 dB(A) | 41 (1,172) | 3/8 (10) | 3/8" NPT | 5/8"-11 Male | 4 (1.8) | 11-11/16 (296) | 3-3/4 (95) |
| 52562 | 1 (744) | 9,000 | 77 dB(A) | 39 (1,116) | 3/8 (10) | 3/8" NPT | 5/8"-11 Male | 4 (1.8) | 11-11/16 (296) | 3-3/4 (95) |
| 52564 | 1 (744) | 9,000 | 77 dB(A) | 39 (1,116) | 3/8 (10) | 3/8" NPT | M14x2 Male | 4 (1.8) | 11-11/16 (296) | 3-3/4 (95) |
| 52565 | 1 (744) | 11,000 | 76 dB(A) | 41 (1,172) | 3/8 (10) | 3/8" NPT | M14x2 Male | 4 (1.8) | 11-11/16 (296) | 3-3/4 (95) |

Tune-Up Kit: No. 96532 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)