

ELECTRIC DRILL MOTOR DME22SU★★

CORE DRILLING UP TO Ø 180 MM



3-speed gearbox for optimal rotational speed



Dry drilling with enclosed M16-adaptor



Packed in a handy carrying case

- Ideal for electrical and plumbing installations
- Easy to use with adjustable side handle and soft start
- Optimal rotational speed due to 3-speed gearbox and variable speed adjustment
- Working safely due to integrated overload protection and PRCD switch
- Possibility of dry drilling with enclosed M16-adaptor

TYROLIT

Technical data

DRILL MOTORS		DME22SU**	
Voltage/Frequency	230 V / 50-60 Hz	110 V / 50-60 Hz	
Type no.	10993027	10993028	
Drill diameter range	20-180 mm		
Nominal power	2.2 kW		
Nominal current	9.5 A	18 A	
Load speed	400/750/1550 1/min		
No load speed	850/1650/3450 1/min		
Motor cooling	Air		
Tool attachment (external)	1 ¼"		
Tool attachment (internal)	½"		
Operation	Hand-held rig-based		
Application	Wet dry		
Electronic overload cut-out	•		
Mechanical overload cut-out	•		
PRCD protection switch	•		
Drill rig attachment	Clamping collar 60 mm		
DIMENSIONS & WEIGHT			
Length	552 mm		
Width	110 mm		
Height	150 mm		
Weight	6.0 kg		

System & Accessories

CORE DRILLING SYSTEM WITH DRU160*** DRILL RIG		
10993027	El. Drill motor DME22SU**	
10987400	Drill rig DRU160***	
977619	Fastening bolt assembly	
ACCESSORIES		
400439	Extension 1/2" 100 mm	
359475	Extension 1/2" 200 mm	
359476	Extension 1/2" 300 mm	
889232	Extension 1/2" 400 mm	
707230	Extension 1/2" 500 mm	
378198	Extension 1 1/4" 100 mm	
359471	Extension 1 1/4" 200 mm	
359472	Extension 1 1/4" 300 mm	
359473	Extension 1 1/4" 400 mm	
359474	Extension 1 1/4" 500 mm	
10983964	Dust vacuum adaptor M16	
10983845	Centering spike 120 mm	
10986189	Centering spike 233 mm	
10986190	Strap wrench	